

Safety information for Lithium-Ion batteries

Date of issue: 10/12/2018

Revision date: 10/12/2018

Supersedes: 03/05/2018

Version: 7.16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name

Hilti B 7/1.5 Li-Ion (01), Hilti B 7/2.0 Li-Ion (01), Hilti B 12/2.6 Li-Ion (01), Hilti B 12/4.0 Li-Ion (01), Hilti B 14/1.6 Li-Ion (01), Hilti B 14/2.6 Li-Ion (01), Hilti B 14/3.3 Li-Ion (01), Hilti B 14/5.2 Li-Ion (01), Hilti B 18/1.6 Li-Ion (01), Hilti B 18/2.6 Li-Ion (01), Hilti B 18/2.6 Li-Ion (02), Hilti B 18/3.3 Li-Ion (01), Hilti B 22/1.6 Li-Ion (01), Hilti B 22/2.6 Li-Ion (01), Hilti B 22/2.6 Li-Ion (02), Hilti B 22/3.0 Li-Ion (01), Hilti B 22/3.3 Li-Ion (01), Hilti B 22/3.0 Li-Ion (01), Hilti B 22/3.3 Li-Ion (01), Hilti B 22/3.0 Li-Ion (01), Hilti B 36/2.4 Li-Ion (01), Hilti B 36/2.6 Li-Ion (02), Hilti B 144/2.6 Li-Ion (01)

Relevant identified uses of the substance or mixture and uses advised against

Rechargeable Lithium Ion battery for power tools

Manufacturer/Supplier

Supplier Hilti Far East Private Ltd. No 20 Harbour Drive, #06-06/08 PSA Vista 117612 Singapore - Singapur T +65 6777 7887 - F +65 6777 3057 sg-customerservice@hilti.com Department issuing data specification sheet Hilti Entwicklungsgesellschaft mbH Hiltistraße 6 86916 Kaufering - Deutschland T +49 8191 906310 - F +49 8191 90176310 anchor.hse@hilti.com

SECTION 2: Hazards identification

For the battery chemical materials are stored in a hermetically sealed metal case, designed to withstand Temperatures and pressures encountered during normal use. As a result, during normal use there is no physical danger of ignition or explosion and chemical danger of hazardous materials leakage.

It may cause heat generation or electrolyte leakage if battery terminals contact with other metals. Electrolyte is flammable. In case of electrolyte leakage move the battery from fire immediately.

However if exposed to a fire, added mechanical shocks, decomposed, added electric stress by miss-use, the gas release vent will be operated. The battery case will be breaked at the extreme, hazardous materials may be released.

Moreover, if heated strongly by a surrounding fire, acrid gas may be emitted.

SECTION 3: Composition/information on ingredients

Lithium Ion rechercheable battery pack: Name/Type Energy content (Wh)

B 7 / 1.5 Li-lon (01)	10,8
B 7 / 2.0 Li-lon (01)	14,4
B 12 / 2.6 Li-lon (01)	28,1
B 12 / 4.0 Li-lon (01)	42,66
B 14 / 1.6 Li-lon (01)	23
B 14 / 2.6 Li-lon (01)	36
B 14 / 3.3 Li-lon (01)	48
B 14 / 5.2 Li-lon (01)	73,4
B 18 / 1.6 Li-lon (01)	34,6
B 18 / 2.6 Li-lon (01)	56,2
B 18 / 2.6 Li-lon (02)	56,2
B 18 / 3.3 Li-lon (01)	71,3
B 22 / 1.6 Li-lon (01)	34,6
B 22 / 2.6 Li-lon (01)	56,2
B 22 / 2.6 Li-lon (02)	56,2
B 22 / 3.0 Li-lon (01)	64,8
B 22 / 3.3 Li-lon (01)	71,3
B 22 / 4.0 Li-lon (01)	86,4
B 36 / 2.6 Li-lon (02)	93,6
B 36 / 2.4 Li-lon (01)	86,4



Safety information for Lithium-Ion batteries

B 144 / 2.6 Li-lon (01) 37,44

This product contains a positive electrode (Lithium cobalt oxide (CAS-No. 12190-79-3)), a negative electrode (graphite (CAS-No. 7782-42-5)) and electrolyte (ethylene carbonate(CAS-No. 96-49-1), diethyl carbonate (CAS-No. 105-58-8) and lithium hexafluorophosphate (CAS-No. 21324-40-3)). The physical form of the product, however, precludes exposure to workers under normal conditions of use.

SECTION 4: First aid measures

Description of first aid measures	
First-aid measures general	If the electrolyte is leaking out of the battery pack, the following measures have to be taken.
First-aid measures after inhalation	Assure fresh air breathing. Allow the victim to rest.
First-aid measures after skin contact	Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

Most important symptoms and effects, both acute and delayed			
Symptoms/effects	Not expected to present a significant hazard under anticipated conditions of normal use.		

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures				
Extinguishing media				
Suitable extinguishing media	Cool batteries and accumulators with water jet. Water spray. Foam. Dry powder. Carbon dioxide. Sand.			
Special hazards arising from the substance	e or mixture			
No additional information available				
Advice for firefighters				
Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.			
Protection during firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.			

Personal precautions, protective equipment and emergency procedures				
General measures	No flames, no sparks. Eliminate all sources of ignition. Isolate from fire, if possible, without unnecessary risk.			
For non-emergency personnel				
Emergency procedures	Evacuate unnecessary personnel.			
For emergency responders				
Protective equipment	Equip cleanup crew with proper protection.			
Emergency procedures	Ventilate area.			

Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

SECTION 6: Accidental release measures



Safety information for Lithium-Ion batteries

Methods and material for containment and cleaning up

Methods for cleaning up Other information Take up liquid spill into absorbent material. Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

Precautions for safe handling	
Procentions for sofe bandling	Do

Precautions for safe handling	Do not soak in water or seawater. Do not expose to strong oxidizers. Do not give a strong mechanical shock or fling. Never disassemble, modify or deform. Do not connect the positive terminal to the negative terminal with electrically conductive material. Use only the chargers / electric tools specified by Hilti to charge or discharge the battery.
	Do not throw into fire or expose to high temperatures (>85 °C). Do not connect the positive terminal to the negative terminal with electrically conductive material.
Hygiene measures	Always wash hands after handling the product.
Conditions for safe storage, inclu-	ding any incompatibilities
Storage conditions	Avoid direct sunlight, high temperature, high humidity. Store in a cool place (temperature: -20 °C ~ 40 °C, humidity: 45 - 85%).
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	-20 - 40 °C
Information on mixed storage	Store away from water.

Do not store together with electrically conductive materials.

The accu-pack should be stored at 30 to 50% of the charging capacity. Avoid storing in places where it is exposed to static electricity.

SECTION 8: Exposure controls/personal protection

Exposure controls

Appropriate engineering controls		If the electrolyte is leaking out of the battery pack, the following measures have to be taken.		
Personal protective equipment		Avoid all unnecessary exposure.		
Hand protection		Wear protective gloves.		
Туре	Material	Permeation	Thickness (mm)	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12	EN 374

Eye protection



Other information

Do not eat, drink or smoke during use.

Chemical goggles or safety glasses



Safety information for Lithium-Ion batteries

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance Colour Explosive properties plastic case. red. Black. Risk of explosion by shock, friction, fire or other sources of ignition.

Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity

No additional information available

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

Heating may cause a fire or explosion.

Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Water, humidity.

Incompatible materials

Conductive materials, water, seawater, strong oxidizers and strong acids.

Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

Information on toxicological effects

Potential adverse human health effects and symptoms	This product contains an organic electrolyte. If the electrolyte is leaking out of the battery pack, the following effects are known when getting into contact: Irritation: severely irritant to eyes. Irritation: may cause irritation to the respiratory system.
Other information	When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

SECTION 12: Ecological information				
Additional information	Do not allow battery packs to penetrate the soil.			
	The battery cell may corrode and electrolyte may leak.			

13.1. Waste treatment methods			
Product/Packaging disposal recommendations	Dispose in a safe manner in accordance with local/national regulations. Refer to manufacturer/supplier for information on recovery/recycling.		
Ecology - waste materials	Avoid release to the environment.		
European List of Waste (LoW) code	16 06 05 - other batteries and accumulators 20 01 34 - batteries and accumulators other than those mentioned in 20 01 33		

SECTION 13: Disposal considerations



Safety information for Lithium-Ion batteries

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	ΙΑΤΑ	RID			
UN number						
3480	3480	3480	3480			
UN proper shipping name		·	·			
LITHIUM ION BATTERIES	LITHIUM ION BATTERIES	Lithium ion batteries	LITHIUM ION BATTERIES			
Transport document descript	ion	·	·			
UN 3480 LITHIUM ION BATTERIES, 9A, (E)	UN 3480 LITHIUM ION BATTERIES, 9					
Transport hazard class(es)						
9A	9A	9A	9A			
Packing group						
Not applicable	Not applicable	Not applicable	Not applicable			
Environmental hazards						
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No			
No supplementary information available						

Special precautions for user

- Overland transport

Classification code (ADR) Special provisions (ADR) Limited quantities (ADR) Packing instructions (ADR) Transport category (ADR)	M4 188, 230, 636b, 376, 377 0 P903, P908, P909 2	
Tunnel restriction code (ADR)	E	
- Transport by sea		
Special provisions (IMDG)	188, 230b, 376, 377	
Limited quantities (IMDG)	0	
Packing instructions (IMDG)	P903, P908, P909	
EmS-No. (Fire)	F-A	
EmS-No. (Spillage)	S-I	
Stowage category (IMDG)	A	
MFAG-No	147	
- Air transport		
PCA packing instructions (IATA)	965	
PCA max net quantity (IATA)	5kg	
CAO packing instructions (IATA)	965	
Special provisions (IATA)	A88, A99, A154, A164, A183	



Safety information for Lithium-Ion batteries

- Rail transport

Special provisions (RID) Limited quantities (RID) Packing instructions (RID) Carriage prohibited (RID) 188, 230, 636b, 376, 377 0 P903, P908, P909 No

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No additional information available

SECTION 15: Regulatory information

No additional information available

SECTION 16: Other information

Indication of changes:			
14.3	Danger labels (ADR)	Modified	
14.3	Danger labels (IMDG)	Modified	
14.3	Hazard labels (IATA)	Modified	
14.3	Danger labels (RID)	Modified	

Safety information for Lithium-Ion batteries

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product